

SCRU™ 2®
True headless screw

- True headless screw!
- Cannulated over 1 mm KW
- Compressive
- Dual pitch
- Self drilling
- Self taping



Case from: Michel Merle, M.D.



Design: e-monceaux.fr / 001 Ed.11 - © AREX® - 2019

DISTRIBUTED BY

CE 0459

Manufacturier:
AREX®
3 allée du Clos Tonnerre
91120 Palaiseau FRANCE

www.arex.fr

SCRU™ 2® LOW PROFILE

2.5 mm ø top of the first thread
2.3 mm ø top of the second thread



SCRU™ 2® STANDARD

3 mm ø top of the first thread
2.5 mm ø top of the second thread



REFERENCES

Length	Standard	Low Profile
10 mm	P2P10	-
15 mm	P2P15	-
20 mm	P2P20	P2P20LP
25 mm	P2P25	P2P25LP
30 mm	P2P30	P2P30LP
35 mm	P2P35	P2P35LP
40 mm	P2P40	P2P40LP
45 mm	P2P45	P2P45LP

HOW AND WHY IT WORKS

SCREW PENETRATING TIP
Self Drilling - Self Taping
S: 3mm ø top of the thread
LP: 2.5mm ø top of the thread

SECOND THREAD
Self Compressive
S: 2.5mm ø top of the thread
LP: 2.3mm ø top of the thread



www.arex.fr/QRc.php?c=15

